

COFRAGREASE CL 00

Semi fluid grease NLGI 00 for centralised greasing industrial or automotive systems, and for some industrial reduction gears

APPLICATIONS

- Trucks & Industrial centralized greasing systems
- Low loaded industrial gears

MAIN PROPERTIES

- Water resistant
- Pressure-loadable
- Adhesive
- Temperature stable
- Wear reducing
- Defined corrosion protection
- Suitable for low temperatures
- Good pumpability in central lubricating systems
-

SPECIFICATIONS

- Mercedes Benz MB- 6833.00, sheet 264
- MAN 283 LI-P000

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUES	METHODS
Classification		GP 00/000 G-40 ISO L-X-DBIB 00/000	DIN 51502 ISO 6743-9
NLGI Grade		00 / 000	DIN 51 818
Colour		Green	
Thickening agent		Lithium/Calcium	
Worked penetration (60 strokes)	0.1mm	430-460	DIN ISO 2137
Pour Point	°C	>160	IP 396
Flow pressure at -35°C	hPa	<60	DIN 51 805
Oxidation stability, pressure drop, 100 hrs / 100°C	hPa	<500	DIN 51 808
Base oil viscosity at 40°C at 100°C	mm ² /s	43 6	DIN 51 562-1
Temperature range	°C	-40 to +110°C	DIN 51 826