

## SINTOLUX FORCE V 5W-30

*Low SAP Long drain Engine oil for VW-Audi and other vehicles*

### SPECIFICATIONS

Specifications : ACEA C3  
ACEA C2 (\*)  
API SN

OEM approvals : VW 504 00 / 507 00

Recommandations : BMW LONGLIFE-04  
CHRYSLER MS-11106  
FIAT 9.55535-S3  
MB 229.51/229.52  
PORSCHE C30

### APPLICATIONS

SINTOLUX FORCE V 5W-30 was developed for VW Gasoline & Diesel engines and formulated for compatibility with exhaust after treatment devices and turbochargers, and to achieve outstanding Fuel Economy characteristics.

It can be used in VW vehicles after 2007 with extended oil drain intervals of 50.000 km or two years.

Many other engines, irrespectively of their make, can use this oil, in particular Diesel engines equipped with particulate filters.

(\*) SINTOLUX FORCE V 5W-30 meets all the engine protection requirements of ACEA C2.

### PROPERTIES

- Reduces ash formation in particulate filters and reduces fuel consumption.
- Increases the lifetime of particulate filters.
- Optimum cold starting, lower oil consumption and minimized exhaust emissions.

### TECHNICAL CHARACTERISTICS

Average Characteristics	Unit	Average Value
SAE Grade		<b>5W-30</b>
Density at 15°C	kg/m <sup>3</sup>	848
Viscosity at 100°C	mm <sup>2</sup> /s	11.75
Viscosity at 40°C	mm <sup>2</sup> /s	62.5
Viscosity Index		155
Flash Point	°C	238
Pour Point	°C	- 45