

Product Information



COFRAN COFRA 15W-40

Ultra High Performance engine oil for 4-stroke gasoline and Diesel engines. Specially designed for mowers, rototillers and compact tractors.

Description

COFRAN COFRA 15W-40 is a multigrade engine oil which can be used in gasoline and diesel engines, with or without turbocharger, and is especially recommended for agricultural applications. COFRAN COFRA 15W-40 ensures an outstanding performance and wear protection throughout the engine's lifetime.

Application

COFRAN COFRA 15W-40 is suitable for gasoline and diesel engines. COFRAN COFRA 15W-40 is miscible and compatible with conventional, branded engine oils. However, mixing with other engine oils should be avoided in order to fully exhaust this product's benefits. A complete oil drain is recommended when converting to COFRAN COFRA 15W-40. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages

- Maintains viscosity throughout the oil drain interval because of its excellent shear stability.
- Good wear resistance.

Recommendations

- API CG-4 / SH
- ACEA E2
- MB 228.1
- MAN M 271
- VOLVO VDS
- MTU DDC TYPE 1
- RENAULT RD
- ZF TE-ML 04P, 07D

Product Information



Typical Characteristics

SAE Grade	SAE J300	15W-40
Density at 20°C	DIN 51757	873 kg/m ³
Kinematic viscosity at 40°C	DIN 53000-1	90.17 mm ² /s
Kinematic Viscosity at 100°C	DIN 53000-1	13.47 mm ² /s
Viscosity Index	DIN ISO 2909	148
Pour Point	DIN ISO 3016	-23 °C
Product Dyeing	DIN 10964	None

Product Information



In all cases, to limit the risk of water contamination (including condensation), store drums and barrels horizontally. Do not expose packaging to strong sunlight or extreme temperatures. The information contained in this data sheet is based on FLF's experience and know-how in the development and manufacture of lubricants and other chemical products to the best of our knowledge. All chemical products must be used in the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). The performance of our products can be influenced by a range of factors, including conditions of use, application methods, operating environment, pre-treatment of components, possible external contamination, etc. For these reasons, a universal recommendation of our products is impossible. The information given in the data sheet represents general, non-binding guidelines and is provided for guidance only. No warranty, express or implied, is given concerning the properties of the product or its suitability for a given application. We therefore recommend consulting an application engineer to discuss application conditions and product performance criteria prior to use. It is the user's responsibility to test the functional suitability of the product and to use it under the appropriate safety conditions. Our products are subject to continuous improvement, with the aim of enhancing performance or bringing them into line with any new regulations. We reserve the right to modify our product ranges, our products and their manufacturing processes, as well as all the provisions of our publications, at any time and without prior notice. This data sheet cancels and replaces all previous editions. We expressly draw the attention of all users to the fact that our product has not been designed and tested for use in the nuclear and aeronautical fields ("embedded" product). Any use of our product in the aforementioned sectors is the sole responsibility of the user. Reproduction in any form requires the prior written consent of FLF, all rights reserved.