

COFRAN PLURA STOU SAE 15W-40

High Performance multifunctional oil (STOU / MFO) for engines, manual gearboxes, wet brakes, hydraulics in tractors and other agricultural equipment.

Description

COFRAN PLURA STOU SAE 15W-40 is a High Performance multifunctional oil (STOU / MFO) for engines, manual gearboxes, wet brakes and hydraulics in tractors and other agricultural equipment. Special additives also provide an outstanding deceleration performance combined with a high capability of noise suppression during the oil drain interval.

Application

COFRAN PLURA STOU SAE 15W-40 is recommended for use in engines, manual transmissions, hydraulic systems, multi-plate differentials, and final drives, with or without wet brakes. COFRAN PLURA STOU SAE 15W-40 can be used in manual transmissions and gear hydraulic systems in agricultural machinery with HD engine oil of type SAE 15W-40 as service recommendation and also in manual transmissions having SAE 80W-90 and API GL-4 as service recommendation. Tractors working with connected equipment should be completely switched to COFRAN PLURA STOU SAE 15W-40.

COFRAN PLURA STOU SAE 15W-40 is miscible and compatible with conventional, branded multifunctional oils. However, mixing with other multifunctional oils should be avoided in order to fully exhaust this product's benefits. A complete oil drain is recommended before converting to COFRAN PLURA STOU SAE 15W-40. For information on product safety and proper disposal

please refer to the latest Material Safety Data Sheet.

Advantages

- Supports reduced variety of products.
- Applicable as all-season lubricant.
- Low oil consumption despite the low viscosity.

Specifications

- API GL-4

Recommendations

- ACEA E2
- API CF-4
- CNH MAT 3525, 3526
- DIN 51524 : HLP (-D)
- FENDT KDM 17/2012
- FNHA 200.00, 201.00
- FORD M2C134-D, M2C159-B/C
- JOHN DEERE JDM J20C
- MASSEY FERGUSON CMS M 1145, 1144, 1143, 1139, 1135
- NH 82009201/2/3
- NH 420A
- SAE J306: 80W-90
- SDFG OU 1391, OT 1891
- STEYR D-401
- ZF TE-ML 06A, 06B, 06C, 07B

Product Information



TYPICAL CHARACTERISTICS

Density at 15°C	DIN 51757	0.886 g/ml
SAE class	SAE J300	15W-40
Kinematic Viscosity at 40°C	DIN 51562-1	100 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	13.5 mm ² /s
Viscosity Index	DIN ISO 2909	135
HTHS	CEC L-36-90	≥ 3,5 mPa*s
Pour Point	DIN ISO 3016	-39 °C
Sulphate ash	ASTM D874	≤ 2,0 % m/m
Product coloring	DIN 10964	none

Product Information



In all cases, to limit the risk of water contamination (including condensation), store drums and barrels horizontally. Do not expose packaging to strong sunlight or extreme temperatures. The information contained in this data sheet is based on FLF's experience and know-how in the development and manufacture of lubricants and other chemical products to the best of our knowledge. All chemical products must be used in the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). The performance of our products can be influenced by a range of factors, including conditions of use, application methods, operating environment, pre-treatment of components, possible external contamination, etc. For these reasons, a universal recommendation of our products is impossible. The information given in the data sheet represents general, non-binding guidelines and is provided for guidance only. No warranty, express or implied, is given concerning the properties of the product or its suitability for a given application. We therefore recommend consulting an application engineer to discuss application conditions and product performance criteria prior to use. It is the user's responsibility to test the functional suitability of the product and to use it under the appropriate safety conditions. Our products are subject to continuous improvement, with the aim of enhancing performance or bringing them into line with any new regulations. We reserve the right to modify our product ranges, our products and their manufacturing processes, as well as all the provisions of our publications, at any time and without prior notice. This data sheet cancels and replaces all previous editions. We expressly draw the attention of all users to the fact that our product has not been designed and tested for use in the nuclear and aeronautical fields ("embedded" product). Any use of our product in the aforementioned sectors is the sole responsibility of the user. Reproduction in any form requires the prior written consent of FLF, all rights reserved.