

COFRAN SINTOLUX POWER 10W-30

High-performance synthetic lubricant for passenger cars with gasoline engines.

Description

COFRAN SINTOLUX POWER 10W-30 is a high-performance synthetic lubricant for passenger cars with gasoline engines with or without turbocharger. COFRAN SINTOLUX POWER 10W-30 was developed based on selected base oils and state-of-the-art additive technology.

Application

COFRAN SINTOLUX POWER 10W-30 is recommended for use in all vehicles with normally aspirated, turbocharged and supercharged gasoline engines. Additives provide the lubricant with viscometric and oxidation resistance; they reduce oil thickening and varnish formation in the engine. Due to its low viscosity at high temperature, COFRAN SINTOLUX POWER 10W-30 offers a high potential for reduced fuel consumption.

Advantages

- High Viscosity Index thus ideal viscosity at all operating temperatures.
- Excellent anti-wear protection.
- Prevents foam formation.
- In addition, the formation of sludge, deposits, corrosion and wear is effectively prevented.
- Helps maintain fuel economy.
- Improved cold starting and rapid oil circulation.
- Helps reduce emissions.

Specifications

- API SP
- ILSAC GF-6A

TYPICAL CHARACTERISTICS

SAE Grade	SAE J300	10W-30
Density at 15°C	DIN 51757	866 kg/m ³
Kinematic Viscosity at 40°C	ASTM D 445	73 mm ² /s
Kinematic Viscosity at 100°C	ASTM D 445	10.9 mm ² /s
Viscosity Index	ASTM D 2270	133
Flash Point	NF EN ISO 2592	238 °C

Product Information



In all cases, to limit the risk of water contamination (including condensation), store drums and barrels horizontally. Do not expose packaging to strong sunlight or extreme temperatures. The information contained in this data sheet is based on FLF's experience and know-how in the development and manufacture of lubricants and other chemical products to the best of our knowledge. All chemical products must be used in the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). The performance of our products can be influenced by a range of factors, including conditions of use, application methods, operating environment, pre-treatment of components, possible external contamination, etc. For these reasons, a universal recommendation of our products is impossible. The information given in the data sheet represents general, non-binding guidelines and is provided for guidance only. No warranty, express or implied, is given concerning the properties of the product or its suitability for a given application. We therefore recommend consulting an application engineer to discuss application conditions and product performance criteria prior to use. It is the user's responsibility to test the functional suitability of the product and to use it under the appropriate safety conditions. Our products are subject to continuous improvement, with the aim of enhancing performance or bringing them into line with any new regulations. We reserve the right to modify our product ranges, our products and their manufacturing processes, as well as all the provisions of our publications, at any time and without prior notice. This data sheet cancels and replaces all previous editions. We expressly draw the attention of all users to the fact that our product has not been designed and tested for use in the nuclear and aeronautical fields ("embedded" product). Any use of our product in the aforementioned sectors is the sole responsibility of the user. Reproduction in any form requires the prior written consent of FLF, all rights reserved.