

## PLURA PLUS 15W-40

*engine lubricant, for heavy and light petrol and diesel vehicles, even those with extra power, even in hot, humid countries, thanks to its high, stable TBN (Total Base Number).*

### STANDARDS AND SPECIFICATIONS

Specifications:

- **API CH-4 / SJ**

COFRAN recommendations :

- **CATERPILLAR ECF-1a**
- **CUMMINS CES 20077**
- **DEUTZ DQC-II/III**
- **MACK EO-N**
- **MAN 3275**
- **MB 228.1**
- **RENAULT RDL-2**
- **VOLVO VDS-3**
- **MTU 2.0**

### APPLICATIONS

With its enhanced properties, **PLURA PLUS 15W40** is particularly well suited to use in hot and humid climates.

High-performance lubricant for engines in HGVs, generators, earthmoving machinery, etc.

**PLURA PLUS 15W40** is also well suited to petrol engines requiring an API SJ standard, ensuring the simplification demanded by fleet managers.

### ESSENTIAL PROPERTIES

**PLURA PLUS 15W40** offers effective protection against liner polishing.

**PLURA PLUS 15W40** has a high-performance detergent that prevents deposits from forming, high shear resistance and enhanced anti-wear properties.

**PLURA PLUS 15W40** retains its multi-grade character throughout its service life, thus limiting wear during cold starts.

**PLURA PLUS 15W40** has a high and stable level of TBN (Total Base Number) for better protection against wear and corrosion.

### TECHNICAL SPECIFICATIONS

AVERAGE CHARACTERIST ICS	UNIT	AVERAGE VALUE	METHODS
SAE grade		<b>15W-40</b>	
Density at 20°C	kg/m <sup>3</sup>	0.8686	NF EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	99.39	ASTM D 445
Viscosity at 100°C	mm <sup>2</sup> /s	14.12	ASTM D 445
Viscosity index		145	ASTM D 2270
Point Eclair	°C	242	NF EN ISO 2592
TBN	mgKOH/g	14.2	ASTM D 2896
Flow point	°C	-36	ASTM D 7346



The information contained in this leaflet is for guidance only. We reserve the right, without prior notice, to make any changes to the formulation of our products in order to improve their performance or to bring them into line with any new regulations.

**COFRAN F.L.A. Export F-92500 RUEIL-MALMAISON**

**03/2025**