

PLURAPOID EP 85W-140

Lubricant for mechanical transmissions

DEFINITION & ADVANTAGES

PLURAPOID EP 85W-140 is a mineral lubricant for mechanical transmissions adapted for every conditions of use.

PLURAPOID EP 85W-140 possesses excellent stability to shearing and to temperatures

NORMS & SPECIFICATIONS

API GL-4 / GL-5

MIL L 2105 D

VOLVO 97310

ZF TE-ML 05A, 12E, 16D, 21A

APPLICATIONS

Being multigrade and containing EP additives. **PLURAPOID EP 85W-140** is a multipurpose gear oil which can be used equally well for :

- . Mechanical gear boxes
- . Rear axles
- . Transfer boxes, etc.

The high V.I. of **PLURAPOID EP 85W-140** means it can be used whatever the temperature, climate and conditions of use. It allows much greater oil change intervals that those indicated by the manufacturers.

TECHNICAL CHARACTERISTICS

AVERAGE TECHNICAL CHARACTERISTICS	UNITS	AVERAGE VALUE	TEST METHOD
SAE Grade		85W-140	
Specific gravity at 20°C	kg/m ³	908	NFT 60101
Kinematic viscosity at 40°C	mm ² /s	427	NFT 60100
Kinematic viscosity at 100°C	mm ² /s	30.7	NFT 60100
Viscosity index		98	NFT 60136
Flash point	°C	230	NFT 60108
Pour point	°C	-18	NFT 60105