

# PNEUMAX

**Mineral oil for pneumatic equipments**

## APPLICATIONS

Lubrication of the mechanism of pneumatic equipments : High speed pneumatic hammer and Compressed Air Circuits

**PNEUMAX N°1** : Utilization on heavy equipments (such as jack hammers)

**PNEUMAX N°2** : Utilization on light equipments (such as drills, grinders, impact wrenches) for which a viscosity below 46 is needed

## PROPERTIES

- Excellent fluid at low temperatures.
- Highly resistant to extreme pressures and shocks.
- Excellent protection to corrosion.
- Non toxic

## TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUES	
		Pneumax N°1	Pneumax N°2
Specific Gravity at 20°C	kg/m <sup>3</sup>	881	876
Viscosity at 40°C	mm <sup>2</sup> /s	94.4	34.3
Viscosity at 100°C	mm <sup>2</sup> /s	11.1	5.77
Flash Point	°C	220	210
Pour Point	°C	-27	< -15



Les renseignements contenus dans cette notice sont donnés à titre indicatif. Nous nous réservons le droit d'apporter, sans préavis, toutes modifications à la formulation de nos produits dans le but d'en améliorer les performances ou de les mettre en conformité avec toute nouvelle et éventuelle réglementation les concernant.