

REFRIGEL LD -35

Long-Life X-OAT type organic Antifreeze for all Liquid Cooled Internal Combustion Engines in Cars, Vans, Trucks, Buses, Construction and Industrial Machinery.

APPLICATIONS

Ready to use

Can protect engines until -35 ° C.

REFRIGEL LD -35 provides outstanding, long-life corrosion protection. Also offers reliable protection against cavitation, scaling, sludging and foaming at ratios of just 15% vol. Cleans cooling system surfaces increase cooling efficiency.

Product based on X-OAT type organic technology. Do not mix with antifreezes using the mineral technology.

SPECIFICATIONS

Specifications : **ASTM D3306 TYPE I**
ASTM D6210 TYPE I-FF
GB 27943.1-2022

Recommandations : **CNH MAT 3624 / 3724**
CAT GCM34 / CAT EC-1
Chevrolet GMW 3420
DAF 74002
Detroit Diesel DFS93K217
Deutz DQC CB-14
Ford WSS M97B44-D
Fiat 9,55523
GM 6277M
GMW 3420
JLR (STJLR.03.5212)
John Deere JDM H5
Kobelco
Komatsu 07.892 (2017)
MAN 324 Typ SNF
Mahle – Behr
MB 325.3 / DTFR 29C120
Mitsubishi MHI
Perkins
Isuzu - UD Trucks
Skoda 61-0-0257
Yanmar
Volvo VCS-2
VW TL 774-D/F (G12+)

TECHNICAL CHARACTERISTICS

AVERAGE CHARACTERISTICS	UNIT	AVERAGE VALUE	METHODS
Colour		Orange	
Density at 20°C	g/ml	1073	DIN 51757
pH		8,3	ASTM D1287
Boiling Point	°C	>105	ASTM D1120
Pour Point	°C	-35	ASTM D1120
% concentrate		50	

SAFETY PROCEDURE

REFRIGEL LD -35 contains Mono Ethylene Glycol:

- Do not swallow,
- Avoid the contact with the skin,
- Keep out of reach of children,
- Avoid release to the environment.

Maximum recommended storage life : 2 years