

SINTOLUX POWER 10W-30

Synthetic Gasoline Engine Oil for passenger cars

SPECIFICATIONS

Specifications

API SP
ILSAC GF-6A

PROPERTIES

- Manufactured with high-viscosity index, premium-quality, synthetic/hydroprocessed base oils and specially designed performance additives
- Helps minimize engine deposits and wear
- Protects against high-temperature, oxidation, low-temperature gelling, rust, corrosion and foaming
- Fuel savings thanks to its low viscosity
- Optimum cold starting performance, lower oil consumption and minimized exhaust emissions.

APPLICATIONS

SINTOLUX POWER 10W-30 is recommended for use in all vehicles with normally aspirated, turbocharged and supercharged gasoline engines

TECHNICAL CHARACTERISTICS

Average Characteristics	Unit	Average Value
SAE Grade		10W-30
Density at 20°C	kg/m ³	866
Viscosity at 100°C	mm ² /s	10.9
Viscosity at 40°C	mm ² /s	73.0
Viscosity Index		133
Flash Point	°C	238



Les renseignements contenus dans cette notice sont donnés à titre indicatif. Nous nous réservons le droit d'apporter, sans préavis, toutes modifications à la formulation de nos produits dans le but d'en améliorer les performances ou de les mettre en conformité avec toute nouvelle et éventuelle réglementation les concernant.