

## COFRAN PLURA POWER SAE 15W-40

Lubricant for Diesel & Petrol engines in extreme conditions, with a high and stable TBN

### Description

COFRAN PLURA POWER SAE 15W-40 is a mineral oil-based, high performance engine oil. COFRAN PLURA POWER SAE 15W-40 was developed to provide outstanding engine protection even under the most severe conditions, in which it reduces the risk of breakdown and helps extending the engine life.

### Application

COFRAN PLURA POWER SAE 15W-40 is used for a variety of gasoline and Diesel engines and particularly adapted for warm and moist countries, also when high fuel sulfur content is used.

COFRAN PLURA POWER SAE 15W-40 is miscible and compatible with conventional, branded engine oils. However, mixing with other engine oils should be avoided in order to fully exhaust this product's benefits. A complete oil drain is recommended when converting to COFRAN PLURA POWER SAE 15W-40. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

### Advantages

- Additives provide stability and oxidation resistance reducing thickening and varnish formation.
- Enhanced corrosion protection.
- Excellent load carrying capability ensures exceptional wear protection.

### Recommendations

- API SG/CE/CF-4
- CATERPILLAR
- CUMMINS
- PERKINS

# Product Information



## TYPICAL CHARACTERISTICS

SAE Grade	SAE J300	15W-40
Density at 20°C	NF T 60-101	878 kg/m <sup>3</sup>
Kinematic Viscosity at 40°C	DIN 53000-1	94.8 mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	DIN 53000-1	14.27 mm <sup>2</sup> /s
Viscosity Index	NF T 60-136	150
Flash Point, CoC	NF T 60-118	220 °C
TBN	ASTM D 2896	14.6 mgKOH/g

# Product Information



In all cases, to limit the risk of water contamination (including condensation), store drums and barrels horizontally. Do not expose packaging to strong sunlight or extreme temperatures. The information contained in this data sheet is based on FLF's experience and know-how in the development and manufacture of lubricants and other chemical products to the best of our knowledge. All chemical products must be used in the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). The performance of our products can be influenced by a range of factors, including conditions of use, application methods, operating environment, pre-treatment of components, possible external contamination, etc. For these reasons, a universal recommendation of our products is impossible. The information given in the data sheet represents general, non-binding guidelines and is provided for guidance only. No warranty, express or implied, is given concerning the properties of the product or its suitability for a given application. We therefore recommend consulting an application engineer to discuss application conditions and product performance criteria prior to use. It is the user's responsibility to test the functional suitability of the product and to use it under the appropriate safety conditions. Our products are subject to continuous improvement, with the aim of enhancing performance or bringing them into line with any new regulations. We reserve the right to modify our product ranges, our products and their manufacturing processes, as well as all the provisions of our publications, at any time and without prior notice. This data sheet cancels and replaces all previous editions. We expressly draw the attention of all users to the fact that our product has not been designed and tested for use in the nuclear and aeronautical fields ("embedded" product). Any use of our product in the aforementioned sectors is the sole responsibility of the user. Reproduction in any form requires the prior written consent of FLF, all rights reserved.